

Product Data Sheet

FLANGED PURLIN BOLTS WITH NUTS



- Fixed washer for easy installation and increased holding power.
- Material: 4.8 Carbon Steel: Body Zinc Alloy

PRODUCT CODE	SIZE	BOX QUANTITY			
BOLT1230F	12 x 30mm	1000			

ITEM	SAMPLE	STANDARD		TEST RESULT		
		MIN.	MAX.	MIN.	MAX.	
Nut DC	125	27	28	27.86	27.93	
Nut M	125	12.3	12.8	12.59	12.65	
Nut E	125	19.86	1	20.12	20.14	
Nut S	125	17.73	18	17.85	17.91	
L	125	29.58	30.42	29.87	30.2	
K	125	9	10	9.75	9.88	
DC	125	27	28	27.83	27.91	
E	125	19.86	1	20.14	20.16	
S	125	17.73	18	17.84	17.92	

Mechanical Property:					
ITEM	SAMPLES	STANDARD		TEST RESULT	
		MIN.	MAX.	MIN.	MAX.
Tensile Strength (Rm/MPa)	3	420	1	475	488

Surface Finish: EN ISO10684-2004						
SURFACE FINISHED	THICKNESS	SAMPLES	STANDARD		TEST RESULT	
			MIN.	MAX.	MIN.	MAX.
Zinc Plated	Um	3	3		OK	

Disclaimer: Every reasonable effort has been made to ensure that this document is correct at the time of printing. Sure-Fast Industrial Fasteners makes no warranty, expressed or implied, regarding the accuracy of the data or the results to be obtained from the use thereof. The information is supplied solely for your information and consideration and it is the responsibility of the user to comply with all applicable federal, state and local laws and regulations.