

Product Data Sheet

HEX FLANGE HEAD CONCRETE SCREW




- One piece carbon steel non-expansion anchor for fixing into masonry
- Easy installed by drilling suitable pilot hole and driving anchor by hand or drill.
- Remove without damaging base material or use of grinders etc.
- Material: Carbon Steel Available in Zinc Yellow or Galvanised finish.

| PRODUCT CODE | DIAMETER (MM) | LENGTH/WIDTH (MM) | DRILL (MM) | PER BOX | PULL OUT LOAD (KN)₁ | THREAD LENGTH (MM) |
|-----------------|------------------|----------------------|------------|------------|---------------------------|--------------------------|
| 53BTG16150 | 16 | 150 x 27mm Hex | 16 | 10 | 26.477 | 142 |

The figures shown were achieved when product was installed into 30Mpa Concrete

1 A safe working load should not exceed 25% of stated values.

INSTALLATION



Disclaimer: Every reasonable effort has been made to ensure that this document is correct at the time of printing. Sure-Fast Industrial Fasteners makes no warranty, expressed or implied, regarding the accuracy of the data or the results to be obtained from the use thereof. The information is supplied solely for your information and consideration and it is the responsibility of the user to comply with all applicable federal, state and local laws and regulations.